

## GA10 OZONE / PSA AIR DRYER

Rugged, lightweight and compact, the GA10 ozone/dry air generator is an exceptional value. Engineered to connect to a local air source, this economically priced system includes a 5 micron filter regulator with an auto drain and coalescing filter as stand equipment.



GA10 Ozone / PSA Air Dryer	
Ozone Production @10 scfh	1.10 g/hr
Ozone Production @20 scfh	2.67 g/hr
Ozone Production @30 scfh	4.36 g/hr
Compressed Air Pressure	80-125 psi
Maximum Reactor Pressure	6 psi
Compressed Air Inlet (fnpt)	1/4"
Ozone Outlet (tube)	1/4"
Power Requirement	115V, 60 Hz or 230V 50/60Hz
Dimensions	14.5" x 13" x 8.5"
Weight	22 lbs

\*Specifications subject to change without notice.

## G SERIES OZONE GENERATORS

The G Series ozone generators are used with an external oxygen supply. The units are complete with ozone cell, power supply, feed gas pressure regulator, over-temperature protection, feed gas flow switch, stainless steel ozone fittings, variable output control, reactor pressure control, LED visual ozone indicator, air cooled fan, and will accept a 0-10 VDC input.

Model	Ozone Production grams/hr. (lbs/day)	Ozone Concentration (% weight)	Reactor Pressure PSI (bar)	Gas Flow Rate (scfh)	Power Consumption (watts)	Feed Gas Inlet Fitting (inches)	Ozone Outlet Fitting (inches)	Dimensions (H x W x D Inches)	Weight lbs(kg)
G-11	12 (0.6)	5%	12 (0.8)	10	230	1/4" fnpt	1/4"	19 x 17 x 12	44 (20)
G-21	18 (1.0)	6%	12 (0.8)	10	270	1/4" fnpt	1/4"	19 x 17 x 12	49 (22)
G-22	30 (1.6)	8%	12 (0.8)	20	435	1/4" fnpt	1/4"	19 x 17 x 12	51 (23)
G-23	45 (2.4)	8%	12 (0.8)	30	525	1/4" fnpt	1/4"	19 x 17 x 12	53 (24)
G-24	60 (3.2)	8%	12 (0.8)	40	625	1/4" fnpt	1/4"	19 x 17 x 12	55 (25)

\*Voltage: 115V/60Hz or 230V/50-60Hz